



Wallite L2 Wall-mounted Battery



Easy to extend

Modular design enables easily extension from 5.22 kWh to 78.3 kWh



Flexible

Compatible with leading inverters and provides flexible connecting ways to meet energy needs



Reliable

Grade-A LiFePO4 battery & Own-developed BMS



Long Lifespan

Up to 8000 cycles @25 °C, 80% DOD



Convenient

Real-time monitoring / debugging / upgrading / pairing with inverters



Safe Guarded

Pre-charge function for a safe initial connection



Own-developed IoE

WiFi connection and RS485 / CAN communication available



Eco-friendly

Less noise & air pollution, more sustainable

Powering Your Energy Revolution



Wallite L2 Wall-mounted Battery

TECHNICAL PARAMETER

Model	H-W51100
Voltage	51.2 V
Cell Capacity	102 Ah
Battery Capacity	5.22 kWh
Scalability	Max. 15 pcs in parallel (78.3 kWh)
Rated Power	5.22 kW
Max. Charge/Discharge Current	100 A
Peak Discharge Current	150 A @ 2min 25°C
Max. Terminal Overcurrent Capacity	200 A
Degree of Protection	IP65
Charging Temperature	0°C ~ 50°C
Humidity	0% ~ 95 % (No Condensing)
Weight	50 kg
Dimensions (WxDxH)	400x160x580 mm
Cycle Life*	8000
Communication	RS485, CAN / Wi-Fi
Certificate	CE-EMC, UN38.3, MSDS, IEC62619

* Test conditions: 0.5C Charging& Discharging. @25°C, 80% DOD

Compatible inverters



Poweroad Renewable Energy Co., Ltd.

Office: 18th Floor, F5 Building, Xiamen Software Park III, Jimei District, Xiamen, Fujian, China 361023
 Factory: Building 7-1, No. 1068, Jimei North Avenue, Jimei District, Xiamen City, Fujian, China 361023

+86 592 5558101
 sales@poweroad.com
 www.poweroad.com

POWEROAD reserves the right to modify the specifications and features without prior notice.